


Technical Specification

Signature Collection



| Attributes | Standard | Result |
|---------------------------------|--|--|
| Type of floor covering | | Hybrid / Rigid core |
| Installation | | Unilin Click System |
| Core | | SPC |
| Colours | | 8 |
| Size | | 1545mm x 228mm |
| Thickness | | 9.0mm |
| Core thickness | | 7.0mm |
| Wear layer | | 0.5mm |
| Surface Features | | Embossed |
| Backing | | 2mm Acoustic underlay |
| Packaging | | 5 Planks / pack = 1.761m ² |
| Total weight | | 11.5kg/m ² / 23kg per pack |
| Beveled edge | | Micro Bevel Edges |
| Classification | ISO 10874 / EN 685 ISO 10874 / EN 685 | Commercial: light Domestic: heavy |
| Reaction to fire | AS/NZ ISO9239 1-2003 | CHF: ≥10.50kW/m ² Smoke value: 57%.min |
| Slip resistance | AS 4586:2013 Appendix A | P3 |
| Dimensional stability | Heat at 60°C for 24 hours | Length: -0.9% Width: -0.09% |
| Acoustic impact noise reduction | AS/NZ ISO 717.2-2004 | FIIC ^{4,5} = 64 L'nTw ³ = 43 AAAC 5 Star Rating ¹ |
| Underfloor heating | | Suitable for hydronic underfloor heating, max. 27°C |
| VOC Emissions | ASTM D5116-17 Green Building Council of Australia Phthalate Free | Compliant for VOC Yes |
| Quartz content (wt%) | | Not detected |
| Warranty | Commercial Domestic | 10 Years warranty* 25 Years warranty* |

Create Timber Floor

18 Natalia Ave, Oakleigh South VIC 3167 | 03 9558 6191 | info@createtimberfloor.com.au | www.createtimberfloor.com.au