

## Specification Data Sheet

### Village Oak 190 x 14/3 mm & 220 x 14/3mm. Tongue & Groove (T&G).

Village Oak planks are manufactured with a 3mm solid European Oak wear layer permanently bonded to a 11mm mixed hardwood plywood substrate. This trusted method of construction provides a long wearing, stable and durable floor with a finished thickness of 14mm. Ideal for floors, ceilings & walls in residential, multi-residential and commercial construction projects. **Interior use only.**

**Key Features;** Engineered to exacting standards. Manufactured from sustainable natural forest resources. Extremely stable with excellent wear resistance. Wear layer can be re-sanded and rejuvenated throughout the products lifecycle.

**Colour Range;** 190mm – 14 Sku's & 220mm – 8 Sku's - Natural oak, light Scandinavian tones, warm, earthy greys to darker colours.

**Description;** Engineered European Oak, T&G for direct fix, trowel adhesive installation or floating installation.

**Grade & Surface;** A/B/C Grade contains knots and natural characteristics that are filled and patched to compliment surface colour and texture. Pre-finished Matte coating.

**Size & Length;** 190mm width x 14mm thick x 1900mm length, 220mm width, 14mm thick, x 2200mm length. Both sizes contain approx. 30% nested shorter length planks.

**Quantity;** 190mm - 2.166m<sup>2</sup> / carton & 220mm – 1.936m<sup>2</sup> / carton.

**Profile;** Tongue & Groove (T&G) profile. Micro Bevelled Edges.

**Acoustic outcome;** 14mm Timber - Test Result with 2mm Underlay, L'nT,w 42.

**Fire Test Data;** AS/ISO9239.1-2003 14mm - Critical Heat Flux, 3.7kW/m<sup>2</sup>. Mean Smoke Development, 21 percent minutes.

**Slip Resistance;** In accordance with AS/NZS 4586; 2013 P3. **VOC Emissions;** E1, (Below World Health Organisation Levels).

**R-Value Thermal Resistance;** 0.0875. **JANKA Hardness;** 5.5 – 6.0kN.

**Accessories;** Alloy trims, MDF coloured scotia & Stair Nosing available to support colour selection for interior fit-out.

**Pre-finished, - no dust, no smell, and no mess.** Please consult with your supplier for specific site install guidelines prior to installation. For specification or reseller support contact, [info@preferencefloors.com.au](mailto:info@preferencefloors.com.au) or a local sales office.

[www.preferencefloors.com.au](http://www.preferencefloors.com.au)

#### Adelaide (SA)

t +61 8 8262 2774  
sa@preferencefloors.com.au

#### Brisbane (QLD)

t +61 7 3875 1688  
qld@preferencefloors.com.au

#### Melbourne (VIC)

t +61 3 9794 5111  
vic@preferencefloors.com.au

#### Perth (WA)

t +61 8 9471 7785  
wa@preferencefloors.com.au

#### Sydney (NSW)

t +61 2 9738 1188  
sales@preferencefloors.com.au